VERTICAL
POWERDOCK

Vertical Powerdock provides a discrete solution for power, data and USB charging. Now with the PD3 version you can have full connectivity even when lowered!

VERTICAL POWERDOCK

Most commonly used in board-rooms, meeting rooms and breakout areas, our Vertical Powerdock provides an elegant solution for Power, USB Charging, Data and AV sockets on the work surface. Our PD3 version can even be closed whilst in use providing the ultimate discrete solution.

Quick and easy to install the Vertical Powerdocks can be customised to suit individual requirements.

---

1 x UK fused **I** Dual Smart Charge USB **I** 2 x data points **I** 1 x HDMI

41S2-1055H2 Cat5e, 2m
41S2-1055H3 Cat5e, 3m
41S2-1055H3 Cat5e, 5m
41S2-1066H2 Cat6, 2m
41S2-1066H3 Cat6, 3m
41S2-1066H5 Cat6, 5m

1 x UK individually fused **I** Dual Smart Charge USB **I** 2 x data points

42S2-1052 Cat5e, 2m
42S2-1053 Cat5e, 3m
42S2-1055 Cat5e, 5m
42S2-1062 Cat6, 2m
42S2-1063 Cat6, 3m
42S2-1065 Cat6, 5m

---

2 x UK individually fused **I** 2 x data points

422-1052 Cat5e, 2m
422-1053 Cat5e, 3m
422-1055 Cat5e, 5m
422-1062 Cat6, 2m
422-1063 Cat6, 3m
422-1065 Cat6, 5m

2 x UK individually fused **I** 4 x data points

424-1052 Cat5e, 2m
424-1053 Cat5e, 3m
424-10552 Cat5e, 5m
424-1062 Cat6, 2m
424-1063 Cat6, 3m
424-1065 Cat6, 5m

---

3 x UK individually fused **I** 2 x data points

3 x UK individually fused **I** 2 x data points

432-1052 Cat5e, 2m
432-1053 Cat5e, 3m
432-1055 Cat5e, 5m
432-1062 Cat6, 2m
432-1063 Cat6, 3m
432-1065 Cat6, 5m

434-1052 Cat5e, 2m
434-1053 Cat5e, 3m
434-1055 Cat5e, 5m
443-1062 Cat6, 2m
443-1063 Cat6, 3m
434-1065 Cat6, 5m

4 x UK individually fused **I** 2 x data points

4 x UK individually fused **I** 4 x data points

442-1052 Cat5e, 2m
442-1053 Cat5e, 3m
442-1055 Cat5e, 5m
442-1062 Cat6, 2m
442-1063 Cat6, 3m
442-1065 Cat6, 5m

444-1052 Cat5e, 2m
444-1053 Cat5e, 3m
444-10552 Cat5e, 5m
444-1062 Cat6, 2m
444-1063 Cat6, 3m
444-1065 Cat6, 5m

4 x UK individually fused **I** Dual Smart Charge USB **I** 2 x data points

PD3-2S2-1052 Cat5e, 2m
PD3-2S2-1053 Cat5e, 3m
PD3-2S2-1055 Cat5e, 5m
PD3-2S2-1062 Cat6, 2m
PD3-2S2-1063 Cat6, 3m
PD3-2S2-1065 Cat6, 5m

PD3-2S2-1152 Cat5e, 2m
PD3-2S2-1153 Cat5e, 3m
PD3-2S2-1155 Cat5e, 5m
PD3-2S2-1162 Cat6, 2m
PD3-2S2-1163 Cat6, 3m
PD3-2S2-1165 Cat6, 5m

PD3-2S2-1352 Cat5e, 2m
PD3-2S2-1353 Cat5e, 3m
PD3-2S2-1355 Cat5e, 5m
PD3-2S2-1362 Cat6, 2m
PD3-2S2-1363 Cat6, 3m
PD3-2S2-1365 Cat6, 5m

Two fold-flat chromed handles raise the unit out of the work surface and lower it back in

powerbook:

Aluminium cap cover over a rubber seal to protect against liquid spills

15A thermal overload switch protects the product and units connected to it in the case of a power surge

r16mm

270.5 mm

91.1mm

10A 250V~
CAT.No.1CА

10A 250V~
CAT.No.1CА

10A 250V~
CAT.No.1CА

CAT.4

CAT.4

Power outlets can be rotated to any angle in 45º increments

Choose between 24 different international power outlets

Power outlets come with a built-in shutter to protect agains foreign objetcs being plugged in

Peripheral options

⊙	🔲	Cat 6	HDMI	⊙
RCA	USB	DATA	HDMI	Audio/ Mic

Lock release button keeps unit locked in the raised position and releases when pressed to lower into the work surface

Robust locking collar for fast and easy installation

↑

80mm (cut-out size 80mm)

A spring-loaded swivel cap covers a smart charging dual USB port on top of the unit

SMART CHARGING

A smart, dual port USB charger can detect Apple®, Android® and Windows® mobile devices while providing fast charging. It suuports sleep mode charging for most Apple® products and is compatible with USB2.0 and 3.0 portable devices. Maximum 2.1A is available for the dual USB ports

Chromed handle and cable flap from which cables can extend when plugs are left in the outlets of the stowed unit

226 mm

146 mm

16A 250V~
CAT.No.1CR

16A 250V~
CAT.No.1CR

16A 250V~
CAT.No.1CR

16A 250V~
CAT.No.1CR

15A thermal overload switch protects the unit from power overloads

Choose between 24 different international power outlets

Power outlets are oriented to facilitate the exit of cable through the cable flap

Lock release button keeps unit locked in the raised position and releases when pressed to lower into the work surface

Robust locking collar for fast and easy installation

One power outlet is located under the work surface for products that need to be permanently connected

↑

92mm (cut-out size 92mm)